

Express Mail Label No.: **ER 375702249 US**

Deposited with U.S. Postal Service: Tuesday, March 16, 2004

Covered by Express Mail Certificate under 37. C.F.R. 1.10

5

10

15

**NON-PROVISIONAL APPLICATION**

**FOR**

20

**UNITED STATES LETTERS PATENT**

25

Be it known that Francis W. Hughto-Delzer, residing at 2947 Northwood Drive, Endwell, New York 13760; Herbert M. Swan III, residing at 330 Grippen Hill Road, Vestal, New York 13850; Dale Zimmer, residing at 211 Tobey Road, Apalachin, New York 13732, and Peter M. Ziolkowski, residing at 81 Glann, Apalachin, New York 13732, each being a citizen of the United States of America, have invented a new and useful

30

**HIGH-STRENGTH, WEAR RESISTANT SWINGBOLT SUPPORT HOOK AND  
HOOK-AND-SWINGBOLT FASTENER ASSEMBLY INCLUDING A  
HIGH-STRENGTH, WEAR RESISTANT SUPPORT HOOK**

of which the following is a specification.

35

40

## STATEMENT OF UNITED STATES GOVERNMENT RIGHTS IN THE INVENTION

This invention was made with U.S. Government support under contract N00019-97-C-0147 awarded by the United States Navy. The U.S. Government has certain rights in this invention.

5

## BACKGROUND

### 1. Field

Although not so limited in its utility or scope, implementations of the present invention are particularly well suited for tool-less, selectively releasable fastening of the housings of electronics units to trays, shelves and other frameworks carried aboard aircraft, ships and railroads, for example.

### 2. Brief Description of Illustrative Environments and Related Art

Hook-and-swingbolt fastener assemblies are widely employed in various industries including, for example, the selectively releasable securement of ship-board electronics and avionics housings. In a typical implementation, an electronics housing or "box" includes a wall with an exterior surface to which is mounted one or more swingbolt hooks. Each swingbolt hook includes a mounting portion or base that is fastened, adhered or otherwise secured to the housing and a curved catch portion that extends outwardly from the base. Depending from the tray shelf or other framework to which the housing is to be secured is a swingbolt adapted for cooperative securing engagement with each of a selected number of swingbolt hooks depending from the housing.

As shown in the examples of FIGS. A and Bi, a typical swingbolt includes an elongated rod having first and second ends and is externally threaded along at least a portion of its length between the first and second ends. The first end is pivotably anchored to the tray or other framework to which the housing is to be secured by a

clevis, for example. Annularly disposed about the rod is a hook catch which is most commonly configured as a hook-engaging cup that, when not secured in contacting engagement with a hook, is linearly translatable along the rod axis. Situated between the second end of the rod and the cup is an internally threaded swingbolt nut threadably received about the threaded portion of the rod.

The housing of an electronics unit, for instance, is removably mounted in a vehicle by placing the housing on a tray or shelf. Each swingbolt hook of a selected number of swingbolt hooks is aligned for engagement with a swingbolt depending from the tray. Once aligned with a swingbolt hook, a swingbolt is swung into a position (FIG. A) that facilitates the engagement of the annular interior surface of the cup with the swingbolt catch of the hook. The cup and swingbolt catch are then retained in securing engagement by threadably advancing the nut toward the first end of the rod to urge and retain the interior cup surface in engagement with the swingbolt catch. Although the nut can be of a type that is advanced with a tool such as a wrench, swingbolt assemblies are typically designed so as to obviate the need for tools. Accordingly, the nut is either incorporated into a knob or the rod carries a separate knob selectively engageable with the nut. In the particular examples of FIGS. A and B, inwardly projecting flanges depend from an inside knob wall for selective, torque-applying engagement with outwardly projecting flanges depending from the nut.

Hook-and-swingbolt fastener systems have experienced some failures, particularly when used in vehicles subjected to highly turbulent or otherwise harsh environments such as military aircraft. A common point of failure has been in the swingbolt hooks and, more particularly, in the wear and bending and/or breaking off of swingbolt catches from the bases of hooks. Swingbolt hook failures can result in the destruction of very expensive equipment and injuries to personnel.

Accordingly, there exists a need for an improved swingbolt hook less susceptible to failure.

## SUMMARY

In various alternative embodiments, a hook-and-swingbolt fastener system adapted for selectively coupling first and second objects comprises a swingbolt including (i) an elongated rod having a first end pivotably mountable to a first object and a second end longitudinally opposite the first end, (ii) a set of external threads extending along at least a portion of the rod, (iii) a hook catch slidably retained by the rod and adapted for longitudinal translation along the rod, and (iv) an internally threaded nut situated between the second end of the rod and the hook catch such that the nut can be selectively caused to exert a force against the hook catch in the direction of the first end of the rod.

A swingbolt hook adapted for selective cooperative coupling with the swingbolt includes an base having rear and front surfaces and extends longitudinally along a base axis between first and second ends, the rear surface being adapted for mounting in contacting engagement with a surface of the second object (e.g., a framework, a wall or an electronic unit housing). In a typical embodiment, the base axis is defined so as to extend along a mounting plane that, for example, when the hook is mounted to a second object surface, is parallel to a plane defined by the object surface to which the hook is mounted. Depending from the base is a swingbolt catch having base and distal ends and first and second opposed surfaces. Each of the first and second surfaces extends laterally between left and right sides of the swingbolt catch. The first surface furthermore extends between the front surface of the base and the distal end of the swingbolt catch and is adjacent to, and joined through a first transition region with, the front surface of the base. The second surface extends between the rear surface of the base and the distal end of the swingbolt catch and is joined, through a second transition region, with the rear surface of the base.

The first and second surfaces of the swingbolt catch are oriented to one another

such that, as viewed into a first cross-sectional plane passing through the first and second surfaces and between the left and right sides of the swingbolt catch, the first and second surfaces extend along, respectively, first and second catch-surface axes that converge away from the base such that the swingbolt catch increases in thickness between the first and second surfaces with increased proximity to the base. In various versions, the first catch-surface axis defines, with the first base axis, a first angle that is one of (i) 90-degrees and (ii) acute and the second catch-surface axis defines, with the first base axis, a second angle that is more acute than the first angle. Still additional alternative versions are configured such that, as viewed into a second cross-sectional plane passing through the first and second surfaces and the left and right sides of the swingbolt catch, at least one of (i) the first surface of the swingbolt catch is convex and (ii) the second surface of the swingbolt catch is concave.

In order to resist wear and/or corrosion, various embodiments are at least partially coated with a wear-resistant coating such as, by way of non-limiting example, nickel plate, Teflon<sup>®</sup>, or chrome.

Although hook-and-swingbolt fasteners generally facilitate the rapid and convenient releasable securement of one structure to another without the use of tools, typical embodiments of the present invention are particularly well suited for releasably mounting electronic equipment to customized frameworks carried aboard transport vehicles such as, by way of non-limiting example, commercial and military aircraft; ocean-going vessels including ships and submarines; and railroad engines and cars. Examples of the frameworks to which electronic equipment is secured include shelves, racks and trays. It will be appreciated that, although it is more typical for swingbolt hooks mounted to equipment unit housings to cooperatively engage swingbolts depending from the frameworks to which those unit housings are to be secured, implementations in which swingbolts are mounted to unit housings and swingbolt hooks are mounted to frameworks are also within the scope and contemplation of the

invention.

The swingbolt and swingbolt hook cooperate such that, once they are generally aligned with one another along a common plane, for example, the swingbolt is swung into a position that facilitates the engagement of an interior surface of the hook catch with the swingbolt catch of the hook. The "common plane" is, for instance, a plane along which the rod of the swingbolt pivots. When the interior surface of the hook catch is placed in contacting engagement with the swingbolt catch and the nut is threadably advanced toward the first end of the rod so as to exert at least a predetermined minimum force against the hook catch, the swingbolt catch and hook catch are drawn into retaining engagement. Representative, non-limiting embodiments are more completely described and depicted in the following detailed description and the accompanying drawings.

15

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. A depicts an illustrative current hook-and-swingbolt fastener system;

FIGS. Bi and Bii depict front and right side views of an illustrative existing swingbolt hook;

20

FIG. Biii shows the swingbolt hook of FIGS. Bi and Bii fastened to a housing and a swingbolt pivotably mounted to a tray with the swingbolt hook and swingbolt cooperatively coupled to retain the housing and tray in fixed relative positions;

FIG. 1 depicts an illustrative hook-and-swingbolt fastener system wherein the swingbolt hook embodies aspects of the invention;

FIG. 2 shows a front view of an illustrative swingbolt hook;

25

FIG. 2A is a cross-sectional side view of the swingbolt hook depicted in FIG. 2;

FIG. 3 is side view of the hook of FIG. 2;

FIG. 3A is a front cross-section as viewed into a plane passing through the

swingbolt catch of the hook in FIG. 3;

FIG. 4A shows an illustrative hook catch including a collar annularly disposed about the rod of a swingbolt and including a socket with an arcuate interior surface adapted for contacting engagement with the swingbolt catch of a swingbolt hook;

5 FIG. 4B is a side view of the hook catch of FIG. 4A in coupled engagement with the swingbolt catch of a swingbolt hook;

FIG. 4C depicts an alternatively configured illustrative hook catch including a collar annularly disposed about the rod of a swingbolt and including an arm extending outwardly from the collar to a distal end from which depends a tongue with a planar  
10 interior surface adapted for contacting engagement with the swingbolt catch of a swingbolt hook;

FIG. 4D is a side view of the hook catch of FIG. 4C in coupled engagement with the swingbolt catch of a swingbolt hook;

FIG. 5 depicts an alternative illustrative hook-and-swingbolt fastener system  
15 wherein the swingbolt hook embodies aspects of the invention;

FIG. 5A is a view into the cross-sectional plane  $V_A$  as indicated in FIG. 5;

FIG. 5B is a cross-sectional view of a swingbolt catch of rectangular cross section engaging the hook catch of swingbolt; and

FIG. 6 shows a swingbolt hook similar to the swingbolt hook of FIGS. 2A through  
20 3A with a wear-resistant coating.

## DETAILED DESCRIPTION

25 The following description of various embodiments of a hook-and-swingbolt fastener assembly and of a hook adapted for selective coupling with a swingbolt is illustrative in nature and is therefore not intended to limit the scope of the invention or its application of uses.

Referring to FIG. 1, two main components of a hook-and-swingbolt fastener system **50** are a swingbolt **100** and a swingbolt hook **200**. The illustrative swingbolt **100** of FIG. 1 includes an elongated rod **110** extending along a rod axis  $A_R$  between a first end **112** and a second end **114**. The first end **112** of the rod **110** is pivotally anchored to a shelf **300** by a clevis **115**.

Extending at least partially between the first and second ends **112** and **114** of the rod **110** is a set of external threads **120** that threadably receives and retains a nut **130** for alternative threadable advancement toward and away from each of the first and second ends **112** and **114**. A hook catch **140** is slidably retained between the first end **112** of the rod **110** and the nut **130** such that the position of the nut **130** along the threads **120** limits the extent to which the hook catch **140** is slidable along the rod **110** toward to the second end **114** of the rod **110**. The nut **130** is rotated about the threads **120** by a knob **160** that is selectively engageable with the nut **130**.

Referring to FIGS. 1 and 2 through 3A, an illustrative swingbolt hook **200** adapted for selective coupling engagement with the swingbolt **100** includes a base **210** having rear and front surfaces **212** and **214** and extends longitudinally along a base axis  $A_B$  between first and second ends **216** and **218**. The swingbolt hook **200**, as shown in FIG. 1, is mounted by fasteners **225** to a housing **400** with the rear surface **212** of the base **210** in contacting engagement with the exterior surface **415** of the housing wall **410**.

As shown in FIGS. 2 through 3A, depending from the base **210** is a swingbolt catch **250** having base and distal ends **252** and **254** and first and second opposed surfaces **255** and **256**. The first surface **255** extends between the front surface **214** of the base **210** and the distal end **254** of the swingbolt catch **250** and is adjacent to, and joined through a first transition region **260** with, the front surface **214** of the base **210**. The second surface **256** extends between the rear surface **212** of the base **210** and the distal end **254** of the swingbolt catch **250** and is joined, through a second transition



region **262**, with the rear surface **212** of the base **210**. Moreover, each of the first and second surfaces **255** and **256** extends laterally between left and right sides **258** and **259** of the swingbolt catch **250**.

Referring to FIGS. 2 and 2A, as viewed into a first cross-sectional plane  $P_{CS1}$  passing through the first and second surfaces **255** and **256**, and between the left and right sides **258** and **259**, of the swingbolt catch **250**, the first and second surfaces **255** and **256** of the swingbolt catch **250** extend along, respectively, first and second catch-surface axes  $A_{C1}$  and  $A_{C2}$ . The first and second catch-surface axes  $A_{C1}$  and  $A_{C2}$  converge away from the base **210** such that the swingbolt catch **250** increases in thickness between the first and second surfaces **255** and **256** with increased proximity to the base **210**. In various versions, the first catch-surface axis  $A_{C1}$  defines, with the base axis  $A_B$ , a first angle  $\theta_1$  that is one of (i) 90-degrees and (ii) acute and the second catch-surface axis  $A_{C2}$  defines, with the base axis  $A_B$ , a second angle  $\theta_2$  that is more acute than the first angle  $\theta_1$ .

Referring to FIGS. 3 and 3A, in order to accommodate the rod **110** of the swingbolt **100**, the second surface **256** of the swingbolt catch **250** in some embodiments is concave as viewed into a second cross-sectional plane  $P_{CS2}$  passing through the first and second surfaces **255** and **256** and the left and right sides **258** and **259** of the catch **250**. Irrespective of the contour of the second surface **256** of the catch **250**, some versions include a catch **250** having a convex first surface **255** such as the illustrative versions of FIGS. 2 through 3A.

In the particular embodiment of FIG. 1, the hook catch **140** typifies extant swingbolts in that it is in the form of a cup **142** having an interior surface **144** annularly disposed about the rod **110**. Although a cup **142** simplifies the coupling of the swingbolt **100** with a swingbolt hook **200** because no particular rotational alignment -- about the rod axis  $A_R$  -- of the hook catch **140** with a swingbolt catch **250** is required, it is to be understood that swingbolts having alternatively configured hook catches **140** are within

the scope and contemplation of the invention. FIGS. 4A and 4B and 4C and 4D depict non-limiting examples of alternatively configured hook catches **140**. FIGS. 4A and 4B depict, respectively, end and side views of a hook catch **140** having a collar **146** annularly disposed about the rod **110**. Depending from the collar **146** is a socket **147** having an arcuate interior surface **148** adapted for engaging the first surface **255** of the swingbolt catch **250** of a swingbolt hook **200**. FIGS. 4C and 4D depict, respectively, end and side views of a hook catch **140** that, like the example of FIGS. 4A and 4B, includes a collar **146** disposed about the rod **110**. Depending from the collar **146** is an arm **152** that extends along an arm axis  $A_A$  orthogonal to the rod axis  $A_R$  between collar and distal ends **154** and **155**. Extending from the arm **152**, in a location more proximate to the distal end **155** than the collar end **154**, is a tongue **157** having an interior surface **158** adapted for selective engagement with the first surface **255** of the swingbolt catch **250** of a swingbolt hook **200**. The interior surface **158** may, in alternative versions, be planar, concave, keyed for mating with one or more grooves or tongues in the first surface **255** of the swingbolt catch **250** of a hook **200** or otherwise contoured.

In various versions, the catch **250** of a swingbolt hook **200** includes a convex first surface **255** for receiving, for example, (i) the annular interior surface **144** of a cup **142** such as that shown in FIG. 1 or (ii) the arcuate interior surface **148** of a hook catch **140** including a socket **147** with an arcuate interior surface **148** such as that shown in the examples of FIGS. 4A and 4B.

Embodiments of a hook-and-swingbolt fastener system **50** within the scope of the invention are used in substantially the same manner as described in the background section of the specification in connection with an illustrative, previously extant swingbolt fastener system. In light of the previous explanation and in light of the fact that the use of such fastener systems is reasonably apparent, a detailed explanation of the use of an embodiment of a hook-and-swingbolt fastener system **50** embodying aspects of the invention is not provided. However, certain aspects are more fully appreciated by

reference to the operative, fastened position of an illustrative embodiment as shown in FIGS. 5 and 5A. As shown in FIG. 5, the illustratively embodied swingbolt hook **200** includes a swingbolt catch **250** having a concave second surface **256** into which, as seen also in the cross-sectional view of FIG. 5A, a portion of the rod **110** is received when the swingbolt **100** and swingbolt hook **200** are cooperatively coupled. Moreover, the convex first surface **255** of the swingbolt catch **250** facilitates contacting engagement with the annular interior surface **144** of the cup **142**.

In addition to facilitating engagement between the first surface **255** of the swingbolt catch **250** and the annular or arcuate interior surface **144** or **148** of a hook catch **140** and accommodating a portion of the rod **110**, a convex first surface **255** and concave second surface **256** increase the strength of the swingbolt catch **250** relative to alternatively configured swingbolt catches **250**. Reference to FIG. 5B facilitates an appreciation for this observation. The swingbolt catch **250** in FIG. 5B is rectangular in cross section and of a maximum width comparable to that of the swingbolt catch **250** in FIG. 5A; in all other respects, the relevant components of the hook-and-swingbolt fastener system **50** of FIG. 5B are the same as those of FIG. 5A. In order to fit into the void between the rod **110** and the interior surface **144** of the cup **142**, the swingbolt catch **250** in FIG. 5B is substantially thinner between the first and second surfaces **255** and **256** than the swingbolt catch **250** of FIG. 5A. Moreover, even if as to swingbolt catches **250** of equal thickness, one that is arch-like is stronger than one that is rectangular in cross-section. Accordingly, for a given material, the swingbolt catch **250** of FIG. 5A is stronger than the swingbolt catch of FIG. 5B on both grounds of material thickness and geometry.

As shown in FIG. 5B, swingbolt catches having convex first surfaces and concave second surfaces are not entirely absent from the universe of pre-existing swingbolt hooks. However, swingbolt hooks **200** including features of the present invention embody a third strength-increasing dimension as shown in FIGS. 1, 3A and 5, and

explained above in association with FIG. 3A; the rearward sloping of the second surface **256** of the swingbolt catch **250** away from the first catch-surface axis  $A_{C1}$  along a second catch-surface axis  $A_{C2}$  that extends along, though not necessarily parallel to, the rod axis  $A_R$  of the swingbolt **100** with which the swingbolt hook **200** is coupled substantially increases the cross-sectional area of material from which the catch is fabricated.

Shown in FIG. 6 is a swingbolt hook **200** including a wear-resistant coating **270**. Illustrative, non-limiting examples of suitable wear-resistant coatings include nickel plate, Teflon<sup>®</sup> and chrome.

The foregoing is considered to be illustrative of the principles of the invention. Furthermore, since modifications and changes to various aspects and implementations will occur to those skilled in the art without departing from the scope and spirit of the invention, it is to be understood that the foregoing does not limit the invention as expressed in the appended claims to the exact construction, implementations and versions shown and described.